

溶融亜鉛メッキ（ドブメッキ）

DBB スチール製	ボルト寸法			スリーブ寸法		取付物 最大厚 (mm)	ドリル径 (mm)	埋込長さ (mm)	穿孔深さ (mm)	入数		打込棒 品番	最大 引張強度 (KN)
	ねじの 呼び	全長 (mm)	ネジ長さ (mm)	外径 (mm)	全長 (mm)					小箱 (本)	大箱 (本)		
DBB-0865	M8	65	35	12.0	35	14	12.5	35	38	200	800	BBT-25	16.6
DBB-1070	M10	70	35	14.0	40	10	14.5	40	45	100	400	BBT-30	21.4
DBB-1080		80	45			20							
DBB-1010		100	65			40							
DBB-1012		120	85			60							
DBB-1015		150	115			90							
 DBB-1210	M12	100	50	17.3	50	26	18.0	50	60	50	200	BBT-40	32.6
DBB-12125		125	75			46							
DBB-1216		160	110			86							
DBB-1220		200	150			126							
DBB-1225		250	205			176				25	100		
DBB-1610	M16	100	50	21.7	50	21	22.0	50	62	25	100	BBT-50	35.9
 DBB-16125		125	75	21.7	60	31	22.0	60	72				37.6
DBB-1616		160	110			71							
DBB-1620		200	145			111							
DBB-1625		250	195			161				15	60		
DBB-2016	M20	160	93	25.4	80	40	26.0	80	90	20	80	BBT-60	59.6
DBB-2017		170	100	27.2	75	52	28.0	75	88	30	—		60.9
DBB-2020		200	130	25.4	80	80	26.0	80	90	15	60		59.6
DBB-3070	W3/8	70	35	14.0	40	9	14.5	40	45	100	400	BBT-30	17.3
DBB-3080		80	45			19			45				
DBB-4100	W1/2	100	50	17.3	50	26	18.0	50	60	50	200	BBT-40	33.6

※溶融亜鉛アルミ合金メッキも対応致します。

※ 引張強度は、社内試験値を表示しています。