

SBB ステンレス製	ボルト寸法			スリーブ寸法		最大 取付物厚 (mm)	ドリル径 (mm)	埋込長さ (mm)	穿孔深さ (mm)	入数		打込棒 品番	最大 引張強度 (KN)		
	ねじの 呼び	全長 (mm)	ネジ長さ (mm)	外径 (mm)	全長 (mm)					小箱 (本)	大箱 (本)				
SBB-0650	M6	50	25	10.5	30	7	11.0	30	33	200	800	BBT-20	12.0		
SBB-0865	M8	65	35	12.0	35	14	12.5	35	38	200	800	BBT-25	15.5		
 SBB-1070	M10	70	35	14.0	40	10	14.5	40	45	100	400	BBT-30	22.5		
 SBB-1080		80	45			20									
SBB-1010		100	65			40									
SBB-1012		120	85			60									
SBB-1015		150	115			90									
 SBB-1210	M12	100	50	17.3	50	26	18.0	50	60	50	200	BBT-40	27.1		
SBB-1212		120	70			46									
SBB-1216		160	110			86									
SBB-1220		200	154			126									
SBB-1610	 M16	100	50	21.7	50	20	22.0	50	62	25	100	BBT-50	35.9		
 SBB-1612		120	70	21.7	60	30	22.0	60	72				15	60	37.8
SBB-1616		160	110			70									
SBB-1620		200	150			110									
SBB-1625		250	190			160									
SBB-2016	M20	160	85	25.4	80	40	26.0	80	90	20	80	BBT-60	45.2		
SBB-2020		200	127			80				15	60				
SBB-3070	W3/8	70	35	14.0	40	9	14.5	40	45	100	400	BBT-30	18.7		
SBB-3080		80	45			19									
SBB-4100	W1/2	100	50	17.3	50	25	18.0	50	60	50	200	BBT-40	31.9		

※ 引張強度は、社内試験値を表示しています。