

SC ステンレス製	ねじ径 (外径)	全長 (mm)	ネジ長さ (mm)	最大 取付物厚 (mm)	ドリル径 (mm)	埋込長さ (mm)	穿孔深さ (mm)	入数		最大 引張強度 (KN)			
								小箱 (本)	大箱 (本)				
SC-645	M6	45	15	6	6.4	30	36 以上	50	800	4.5			
SC-660		60	20	21									
SC-850	M8	50	20	9	8.5	30	38 以上	50	800	12.5			
SC-860		60		19					400				
SC-870		70	25	29									
SC-880		80	30	39									
SC-890		90		49									
SC-810		100	35	61									
SC-1050	M10	50	20	7	10.5	30	40 以上	50	400	14.3			
SC-1060		60	25	12					300	15.5			
SC-1070		70		22									
SC-1080		80		32									
SC-1090		90	30	42									
SC-1010		100		52									
SC-1012		120		72					200				
SC-1260	M12	60	25	9	12.7	35	47 以上	30	240	21.0			
SC-1270		70	25						19				
SC-1280		80		29					45		57 以上	180	
SC-1290		90	30	39									
SC-1210		100	30	59									120
SC-1212		120	35	89									
※ SC-1215		150		89									
SC-1680	M16	80	40	10	17.0	40	56 以上	15	90	22.8			
SC-1610		100		20					17.0	60	76 以上	60	31.1
SC-1612		120		40									
※ SC-1615		150		70									
※ SC-1619		190		110									
※ SC-2013	M20	130	50	25	21.5	80	100 以上	10	40	37.7			
※ SC-2015		150		45									
※ SC-2019		190		85									
SC-3060	W3/8	60	25	11	10.0	35	45 以上	50	400	11.4			
SC-4070	W1/2	70		9	12.7	45	57 以上	30	240	16.1			

※はストレートピンになります。

※ M6 ~ M20・W3/8 は座付きナット仕様
W1/2 はナット・ワッシャ仕様

※ 引張強度は、社内試験値を表示しています。