

ストレートドリル

Straight Shank Drills


HSS

Ox

118°
先端角

N
ねじれ角
(標準)

0.3~7.5mm
10本入
7.6~13.0mm
5本入



ストレートドリル

単位:円(JPY)

サイズ (d)	品 番	全長 (L)	溝長 (ℓ)	定 価
0.3	SD003	19	3	970
0.4	SD004	20	5	800
0.5	SD005	22	6	640
0.6	SD006	24	7	660
0.7	SD007	28	9	600
0.8	SD008	30	10	510
0.9	SD009	32	11	550
1.0	SD010	40	18	460
1.1	SD011	42	20	540
1.2	SD012	42	20	510
1.3	SD013	45	22	540
1.4	SD014	48	23	540
1.5	SD015	48	23	460
1.6	SD016	50	25	500
1.7	SD017	50	25	540
1.8	SD018	52	28	510
1.9	SD019	52	28	510
2.0	SD020	55	29	410
2.1	SD021	55	29	480
2.2	SD022	58	33	480
2.3	SD023	58	33	460
2.4	SD024	61	35	480
2.5	SD025	61	35	410
2.6	SD026	64	37	460
2.7	SD027	64	37	460
2.8	SD028	67	39	450
2.9	SD029	71	42	460
3.0	SD030	71	42	400
3.1	SD031	71	42	540
3.2	SD032	71	42	490
3.3	SD033	73	45	490
3.4	SD034	73	45	510
3.5	SD035	73	45	490
3.6	SD036	76	48	570
3.7	SD037	76	48	570
3.8	SD038	76	48	540
3.9	SD039	79	51	590
4.0	SD040	83	54	540
4.1	SD041	83	54	680
4.2	SD042	83	54	640
4.3	SD043	83	54	680
4.4	SD044	86	56	680
4.5	SD045	86	56	640

サイズ (d)	品 番	全長 (L)	溝長 (ℓ)	定 価
4.6	SD046	86	56	780
4.7	SD047	89	59	780
4.8	SD048	89	59	780
4.9	SD049	92	62	830
5.0	SD050	92	62	750
5.1	SD051	92	62	910
5.2	SD052	95	64	860
5.3	SD053	95	64	910
5.4	SD054	95	64	910
5.5	SD055	95	64	860
5.6	SD056	98	67	1,040
5.7	SD057	98	67	1,040
5.8	SD058	98	67	1,040
5.9	SD059	98	67	1,100
6.0	SD060	102	70	990
6.1	SD061	102	70	1,190
6.2	SD062	102	70	1,190
6.3	SD063	102	70	1,190
6.4	SD064	105	73	1,190
6.5	SD065	105	73	1,120
6.6	SD066	105	73	1,340
6.7	SD067	105	73	1,340
6.8	SD068	105	73	1,340
6.9	SD069	105	73	1,430
7.0	SD070	105	73	1,280
7.1	SD071	108	75	1,630
7.2	SD072	108	75	1,560
7.3	SD073	108	75	1,630
7.4	SD074	111	78	1,630
7.5	SD075	111	78	1,460
7.6	SD076	111	78	1,840
7.7	SD077	114	81	1,780
7.8	SD078	114	81	1,740
7.9	SD079	114	81	1,840
8.0	SD080	114	81	1,590
8.1	SD081	117	84	2,000
8.2	SD082	117	84	1,980
8.3	SD083	117	84	2,000
8.4	SD084	121	87	2,060
8.5	SD085	121	87	1,840
8.6	SD086	121	87	2,250
8.7	SD087	121	87	2,250
8.8	SD088	124	89	2,300

サイズ (d)	品 番	全長 (L)	溝長 (ℓ)	定 価
8.9	SD089	124	89	2,300
9.0	SD090	124	89	2,000
9.1	SD091	124	89	2,520
9.2	SD092	127	92	2,630
9.3	SD093	127	92	2,560
9.4	SD094	127	92	2,630
9.5	SD095	127	92	2,340
9.6	SD096	130	95	2,810
9.7	SD097	130	95	2,810
9.8	SD098	130	95	2,810
9.9	SD099	130	95	3,050
10.0	SD100	130	95	2,560
10.1	SD101	133	98	3,460
10.2	SD102	133	98	3,250
10.3	SD103	133	98	3,250
10.4	SD104	133	98	3,460
10.5	SD105	137	100	2,940
10.6	SD106	137	100	4,080
10.7	SD107	137	100	4,080
10.8	SD108	140	103	4,080
10.9	SD109	140	103	4,080
11.0	SD110	140	103	3,200
11.1	SD111	140	103	4,310
11.2	SD112	143	106	4,130
11.3	SD113	143	106	4,310
11.4	SD114	143	106	4,130
11.5	SD115	143	106	3,620
11.6	SD116	146	109	4,480
11.7	SD117	146	109	4,670
11.8	SD118	146	109	4,480
11.9	SD119	146	109	4,670
12.0	SD120	149	111	3,830
12.1	SD121	149	111	4,880
12.2	SD122	149	111	4,880
12.3	SD123	149	111	4,880
12.4	SD124	152	114	5,100
12.5	SD125	152	114	4,270
12.6	SD126	152	114	5,410
12.7	SD127	152	114	5,190
12.8	SD128	152	114	5,410
12.9	SD129	152	114	5,410
13.0	SD130	152	114	4,440

推奨被削材	構造用鋼 SS400	低炭素鋼 S15C	高炭素鋼 S55C	合金鋼 SCM	調質鋼 HRC25~35	調質鋼 HRC35~40	ステンレス SUS	鋳鉄 FC	タタイル鋳鉄 FCD	アルミニウム合金 AL	銅合金 Cu	チタン合金 Ti
	◎	◎	△	△				○		○	○	