

Bタイプ(振動用)



被削材 ■最適/●適
コンクリート
ブロック・レンガ
モルタル
スレート
ALC
日本壁
石膏ボード
大理石

アンカー穿孔径(mm)


	金属系	その他	接着系
3.4		●	
3.5		●	
4.0		●	
4.3	●	●	
5.0		●	
5.3		●	
5.4	●		
5.5		●	
6.0		●	
6.4	●		
7.5		●	
8.0	●	●	
8.5	●	●	
9.0		●	
9.5	●	●	
10.0	●	●	●
10.5	●	●	
11.0	●		
11.5		●	
12.0	●	●	●
12.5	●	●	
12.7	●		
13.0	●	●	
13.5	●		
14.0		●	●
14.5	●		
15.0		●	
16.0	●	●	●
16.5	●		
17.0	●		
18.0	●	●	
19.0			●
20.0			●
21.5	●		
22.0	●		
24.0		●	
25.0		●	
26.0	●	●	
28.0		●	
32.0		●	

適合電動機
振動ドリル



シャンク形状 ○ ~13mm

豊富に揃ったサイズにより、作業環境ニーズに幅広く対応。




適合電動機
振動ドリル

シャンク形状

○ ~13mm

製品図



特
長

- ▶ 耐久性を重視した超硬チップを採用し、独自設計の刃先形状・角度により、抜群の切れ味を実現。
- ▶ 刃先径:5.0mm以下には、剛性・耐衝撃性に優れたSKS材(合金工具鋼)を選定。ドリルの折れ、曲がりを最小限に抑止。



動画公開中

Bタイプ(ストレート)

プリスターパック

出筋	品番	刃先径 (mm)	全長 (mm)	有効長 (mm)	箱入数 (本)	本体価格[税抜] (1本)
○	B2.5X85BP	2.5	85	50	10	730
	B2.8X85BP	2.8				730
◎	B3.0X85BP	3.0				730
○	B3.2X85BP	3.2				730
◎	B3.4X85BP	3.4				730
◎	B3.5X85BP	3.5				730
△	B3.8X85BP	3.8				730
○	B4.0X85BP	4.0				730
◎	B4.3X85BP	4.3				730
	B4.4X85BP	4.4				730
◎	B4.5X85BP	4.5				730
○	B4.8X85BP	4.8				730
◎	B5.0X85BP	5.0				780
	B5.3X100BP	5.3	100	65	10	780
	B5.4X100BP	5.4				780
○	B5.5X100BP	5.5				780
◎	B6.0X100BP	6.0				830
◎	B6.4X100BP	6.4				830
△	B6.5X100BP	6.5				830
○	B7.0X125BP	7.0	125	75	10	1,040
△	B7.5X125BP	7.5				1,040
○	B8.0X125BP	8.0				1,100
◎	B8.5X125BP	8.5				1,100
△	B9.0X150BP	9.0	150	90	10	1,300
	B9.5X150BP	9.5				1,300
○	B10.0X150BP	10.0				1,300
◎	B10.5X150BP	10.5				1,500
△	B11.0X150BP	11.0				1,500

Bタイプ(ノス)

出筋	品番	刃先径 (mm)	全長 (mm)	有効長 (mm)	箱入数 (本)	本体価格[税抜] (1本)
	B11.5X200	11.5	200	120	6	1,700
○	B12.0X200	12.0				1,700
○	B12.5X200	12.5				1,700
○	B12.7X200	12.7				1,700
	B13.0X200	13.0				1,700
	B13.5X200	13.5				1,800
△	B14.0X200	14.0				1,800
	B14.3X200	14.3				1,950
○	B14.5X200	14.5				1,950
	B15.0X200	15.0				2,050
	B16.0X240	16.0	240	120	6	2,150
	B16.5X240	16.5				2,300
	B17.0X240	17.0				2,300
	B17.5X240	17.5				2,400
△	B18.0X240	18.0				2,600
	B19.0X240	19.0				2,900
	B20.0X240	20.0				3,200
	B21.0X240	21.0				3,500
	B21.5X240	21.5				3,900
	B22.0X240	22.0				3,900
	B23.0X280	23.0	280	140	3	4,400
	B24.0X280	24.0				4,800
	B25.0X280	25.0				5,300
	B26.0X280	26.0				5,700
	B27.0X280	27.0				6,200
	B28.0X280	28.0				6,600
	B30.0X280	30.0				7,300
	B32.0X280	32.0				7,800

Bタイプ・ロング(ストレート)

出筋	品番	刃先径 (mm)	全長 (mm)	有効長 (mm)	箱入数 (本)	本体価格[税抜] (1本)
○	BL4.3X115	4.3	115	70	10	1,070
○	BL3.4X150	3.4	150	90	10	1,120
○	BL3.5X150	3.5				1,120
	BL4.0X150	4.0				1,120
○	BL4.3X150	4.3				1,120
	BL4.5X150	4.5				1,120
	BL4.8X150	4.8				1,120
	BL5.0X150	5.0				1,120
	BL5.3X150	5.3				1,250
	BL5.5X150	5.5				1,250
	BL6.0X150	6.0				1,250
	BL6.4X150	6.4				1,500
	BL4.8X200	4.8	200	120	1	1,350
	BL5.0X200	5.0				1,350
	BL5.5X200	5.5				1,500
	BL6.0X200	6.0				1,500
	BL6.4X200	6.4				1,500
	BL6.5X200	6.5				1,500
	BL7.0X200	7.0				1,600
	BL8.0X330	8.0	330	200	1	1,900
	BL8.5X330	8.5				2,700
	BL9.0X330	9.0				2,700
	BL9.5X330	9.5				2,700
	BL10.0X330	10.0				2,700
	BL10.5X330	10.5				2,900
	BL11.0X330	11.0				2,900

Bタイプ・ロング(ノス)

出筋	品番	刃先径 (mm)	全長 (mm)	有効長 (mm)	箱入数 (本)	本体価格[税抜] (1本)
△	BL12.0X330	12.0	330	200	1	3,000
△	BL12.5X330	12.5				3,200
	BL12.7X330	12.7				3,200
	BL13.0X330	13.0				3,200
	BL14.0X330	14.0				3,200
	BL14.3X330	14.3				3,500
△	BL14.5X330	14.5				3,500
	BL15.0X330	15.0				3,500
	BL16.0X330	16.0	330	200	1	3,500
	BL17.0X330	17.0				3,800
	BL17.5X330	17.5				4,300
	BL18.0X330	18.0				4,300
	BL19.0X330	19.0				4,300
	BL20.0X330	20.0				5,200
	BL21.0X330	21.0				5,200
	BL22.0X330	22.0				5,800
	BL23.0X330	23.0				6,200
	BL24.0X330	24.0				6,200
	BL25.0X330	25.0				6,200

Bタイプ[10本セット]

出筋	品番	刃先径 (mm)	全長 (mm)	有効長 (mm)	1セット入数 (本)	箱入数 (セット)	本体価格[税抜] (1セット)
	DP10-B34	3.4	85	50	10	5	6,300
△	DP10-B35	3.5					6,300
	DP10-B43	4.3					6,300
	DP10-B45	4.5					6,300
	DP10-B48	4.8					6,300
	DP10-B50	5.0					6,800

Bタイプ[5本セット]

出筋	品番	刃先径 (mm)	全長 (mm)	有効長 (mm)	1セット入数 (本)	箱入数 (セット)	本体価格[税抜] (1セット)
○	DP5-B34	3.4	85	50	5	5	3,180
○	DP5-B35	3.5					3,180
△	DP5-B43	4.3					3,180
	DP5-B45	4.5					3,180
	DP5-B48	4.8					3,180
	DP5-B50	5.0					3,500
	DP5-B60	6.0	100	65	5	5	3,700
	DP5-B64	6.4					3,700

Bタイプ[便利サイズ5本セット]

品番	刃先径 (mm)					1セット入数 (本)	箱入数 (セット)	本体価格[税抜] (1セット)
DP-5B	3.4	4.3	4.5	4.8	6.4	5	6	3,500

Bタイプ[便利サイズ3本セット]

品番	刃先径 (mm)					1セット入数 (本)	箱入数 (セット)	本体価格[税抜] (1セット)
DP-3B	4.5	4.8	6.4			3	6	2,300

振動用
コンクリートドリル
[10本セット]振動用
コンクリートドリル
[5本セット]

使用電動ドリル適正回転数

刃先径 (mm)	21.0 以上	800 以下		
11.5 ~ 20.0		800 ~ 1,200		
7.2 ~ 11.0		1,000 ~ 1,500		
5.4 ~ 7.0		1,500 ~ 2,000		
2.5 ~ 5.0		2,000 ~ 2,500		
		500	1,000	1,500 2,000 2,500 回転数 (rpm)

貫通テストデータ



チャックサイズ

ドリル径	2.5 ~ 11.0mm	刃先径に準じたシャンクサイズ	10mm チャック
	11.5 ~ 22.0mm	10mm ノス型シャンク	
	23.0 ~ 40.0mm	13mm ノス型シャンク	13mm チャック